

**PRICES OF HELLO MAKE WIRES & FLEXIBLE CABLES**

| <b>"HELLO" PVC INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL (MULTISTRAND) CABLES FLAME RETARDANT LOW SMOKE (FRLSH) CONFORMING TO IS- 694:2010 WITH BRIGHT ANNEALED ELECTROLYTIC BARE COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</b> |                          |             |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------|-------------|
| <b>SIZE</b>                                                                                                                                                                                                                           | <b>FRLS-H LIST PRICE</b> |             |
| <b>(in Sq.mm)</b>                                                                                                                                                                                                                     | <b>90M</b>               | <b>180M</b> |
| 1                                                                                                                                                                                                                                     | 1750                     | 2980        |
| 1.5                                                                                                                                                                                                                                   | 2650                     | 4500        |
| 2.5                                                                                                                                                                                                                                   | 4450                     | 7450        |
| 4                                                                                                                                                                                                                                     | 6550                     | 11400       |
| 6                                                                                                                                                                                                                                     | 9550                     | 16740       |
| <b>"HELLO" PVC INSULATED AND FRLS ROUND SHEATHED MULTI CORE BRIGHT ANNEALED BARE COPPER CONDUCTOR HEAVY DUTY INDUSTRIAL FLEXIBLE CABLES FOR VOLTAGE GRADE 1100 VOLTS CONFORMING TO IS: 694:2010</b>                                   |                          |             |
| <b>SIZE</b>                                                                                                                                                                                                                           | <b>LIST PRICE</b>        |             |
| 1 x 2 C                                                                                                                                                                                                                               | 4000                     |             |
| 1 x 3 C                                                                                                                                                                                                                               | 5800                     |             |
| 1 x 4 C                                                                                                                                                                                                                               | 7600                     |             |
| 1.5 x 2 C                                                                                                                                                                                                                             | 5600                     |             |
| 1.5 x 3 C                                                                                                                                                                                                                             | 8200                     |             |
| 1.5 x 4 C                                                                                                                                                                                                                             | 10800                    |             |
| 2.5 x 2 C                                                                                                                                                                                                                             | 9000                     |             |
| 2.5 x 3 C                                                                                                                                                                                                                             | 13000                    |             |
| 2.5 x 4 C                                                                                                                                                                                                                             | 17000                    |             |
| 4 x 3 C                                                                                                                                                                                                                               | 19400                    |             |
| 4 x 4 C                                                                                                                                                                                                                               | 25600                    |             |
| 6 x 4 C                                                                                                                                                                                                                               | 37600                    |             |
| 10 x 4 C                                                                                                                                                                                                                              | 62000                    |             |
| <b>HELLO FRLS INSULATED SINGLE CORE UNSHEATHED INDUSTRIAL FLEXIBLE CABLE CONFORMING TO IS 694:2010 WITH BRIGHT ANNEALED COPPER CONDUCTOR FOR VOLTAGE GRADE 1100 VOLTS</b>                                                             |                          |             |
| <b>SIZE</b>                                                                                                                                                                                                                           | <b>LIST PRICE</b>        |             |
| 10 x 1 C                                                                                                                                                                                                                              | 16000                    |             |
| 16 x 1 C                                                                                                                                                                                                                              | 25400                    |             |
| 25 x 1 C                                                                                                                                                                                                                              | 38400                    |             |
| 6 x 3 C                                                                                                                                                                                                                               | 28800                    |             |
| <b>HELLO PVC INSULATED AND PVC SHEATHED INDUSTRIAL 3 CORE FLAT SUBMERSIBLE CABLE WITH BARE BUNCHED COPPER CONDUCTOR FOR SUBMERSIBLE PUMP MOTORS WITH VOLTAGE GRADE 1100 VOLTS AS PER IS:694/2010</b>                                  |                          |             |
| <b>SIZE</b>                                                                                                                                                                                                                           | <b>LIST PRICE</b>        |             |
| 2.5 x 3C                                                                                                                                                                                                                              | 14000                    |             |
| 4 x 3 C                                                                                                                                                                                                                               | 21600                    |             |

✉ enquiry@helloltd.in

🌐 www.helloltd.in

**HELLO CABLES & SWITCHGEARS PVT. LTD**



**"HELLO" PVC INSULATED SINGLE CORE ELECTRONIC CROSS LINKING BEAM CABLE  
(EBXL)**

| <b>SIZE</b>       | <b>FRLS-H LIST PRICE</b> |
|-------------------|--------------------------|
| <b>(in Sq.mm)</b> | <b>90M</b>               |
| <b>1</b>          | <b>2013</b>              |
| <b>1.5</b>        | <b>3048</b>              |
| <b>2.5</b>        | <b>5118</b>              |
| <b>4</b>          | <b>7533</b>              |
| <b>6</b>          | <b>10983</b>             |

**EBXL**

(ZHLS+FR+HR+125°C wires Highest current carrying Capacity Than Any FRLS Wires)

✉ | [enquiry@helloltd.in](mailto:enquiry@helloltd.in)

🌐 | [www.helloltd.in](http://www.helloltd.in)

**HELLO CABLES & SWITCHGEARS PVT. LTD**

